Robertshaw.



Features and Benefits

Automatic Compressor Short Cycle Protection

A system safeguard. Reduces wear and tear of HVAC equipment.

Weekly 5 - 2 Day Programming

Set your weekly program once with four time and temperature settings. The four set points are followed for 5 consecutive days. On the weekend, both mid-day settings are automatically eliminated for all day comfort.

Adjustable Temperature Differential

Maintains optimal customer comfort.

Temporary Program Override

Allows for manual temperature adjustment.

Low Temperature Protection

Heat automatically turns on when temperature goes below 40°F. Protects pipes from freezing.

Toll-Free Assistance

Toll-Free Technical Service number printed right on the thermostat provides immediate assistance.

Quick Wire Terminal Block

Fast and easy installation. Uses sturdy wire clamps – no wrap-around of screws.



PROGRAMMABLE THERMOSTAT





5 - 2 Day Programmable 1 Heat / 1 Cool

Affordable Comfort Control

The Robertshaw 9600 programmable thermostat is the perfect solution to keeping your home comfortable year-round. Not only that, setting back your thermostat twice each day can reduce energy costs up to 25%. **Set it and save.** Today's busy lifestyle demands hands-free temperature control, and with a programmable thermostat, you've got it. At the touch of a button, set your weekly program for summer and winter upon installation. You will always come home to a comfortable setting, and you'll save energy without even thinking about it.

The 9600 is compatible with all standard 24 Volt AC heating and cooling systems.

When you select a Robertshaw thermostat, you've made the choice of an industry partner that's been making quality products for 100 years. Come home to affordable comfort. Come home to Robertshawsm.









9600


PROGRAMMABLE THERMOSTAT





GAS ELECTRIC

Terminal Designations



5 - 2 Day Programmable1 Heat / 1 Cool

THE ROBERTSHAW 9600 REPLACES:

Robertshaw	300-252
White-Rodgers Company*	1F80-51
Honeywell, Inc.*	T8700C, T8112, T8131C T8132C, T8000C, T8001C

^{*} Verify specific application requirements before substitution.

Specifications

Electrical rating: 24 Volt AC (18-30 VAC) 1 amp maximum load per terminal

2 amp total maximum load (all terminals combined) Temperature control range: 45°- 90°F (7°- 32°C)

Accuracy: +/-1°F (+/-.5°C)

DC power: 3.0 VDC (2 "AA" alkaline batteries included) System configurations: 2-5 wire single stage gas, oil,

or electric systems

Terminations: Rh, Rc, W, Y, G

Shipping Information

Indiv. Ctn. Dim.: 6.75" x 4.375" x 1.625"

Master Ctn. Qty.: 6

Master Ctn. Dim.: 9.25" x 5.625" x 7.625"

Master Ctn. Cu. Ft.: 0.23 Master Ctn. Wt.: 4.0 lbs. Max. Pallet Oty.: 1170

Max. Pallet Dim.: 40" x 48" x 48"

Max. Pallet Cu. Ft.: 53.33 Max. Pallet Wt.: 835 lbs.

Other Single-Stage Heat / Cool Thermostats

9200: Mercury-Free Deluxe Mechanical9400: Digital, Non-Programmable9610: Programmable, 7 Day9701i: Deluxe Programmable, 7 Day

(Invensys,...

Climate Controls Americas

515 South Promenade Avenue Corona California 92879-1736 USA Telephone +1 800 304 6563 Facsimile +1 800 426 0804 Outside the USA +1 909 734 2600 Technical Service Telephone +1 800 445 8299 www.icca.invensys.com ©2003 Climate Controls Americas 6/03 - #150-1401H

Distributed by: